

SOLO461 Heat detector test kit

www.boschsecurity.com



BOSCH

Invented for life



- ▶ Operating status display with multi-color LED
- ▶ Automatic detector recognition with infrared sensors
- ▶ Automatic switch-off after 5 min. standby time
- ▶ Automatic switch-off in case of battery overvoltage
- ▶ Enters standby mode after 120 seconds of use

The SOLO461 Heat detector test kit operates with a battery to direct heated air at heat detector sensors. It uses a patented CAT™ (Cross Air Technology) system to focus the air and direct it horizontally at the sensor regardless of the detector's size or shape.

Functions

Cross Air Technology

Under control of a microprocessor, blown air is heated by the element just before exiting the duct. The narrow opening focuses the heated air into a beam. A reference platform incorporated into the Heat Detector Tester ensures that the beam of heated air is correctly lined up with the sensor whatever the shape and size of the detector.

Because the beam of hot air is blown horizontally directly at the sensor:

- Test times are dramatically reduced
- Minimum power is required thereby extending battery life
- The possibility of heat damage to detector plastics is significantly reduced

Tool Operation

When the tool is fully assembled, press the switch on the tester to put the tool into standby mode. When the tester is positioned so that it encloses a detector, the

detector interrupts an infrared beam turning on the heater and blower units in the tester. Hold the tool in place over the detector until either:

- the detector alarms indicating proper operation
- until the tool automatically times out indicating a problem with the detector

When the tool is moved away from the detector or when the tool times out the heater shuts off and the blower runs for a few seconds to cool the heater.



Notice

The SOLO727 charger can only be used with the SOLO770 battery baton. Older chargers (e.g. SOLO726) cannot be used with the SOLO770 battery baton. Older battery batons (e.g. SOLO760) cannot be used with the SOLO727 charger.

Certifications and approvals

Region	Regulatory compliance/quality marks	
Europe	CE	SOLO461
USA	UL	URRQ.S4994, URRQ.S7201 SOLO461

Parts included

Quantity	Component
1	SOLO460 Heat detector tester
2	SOLO770 Battery baton
1	SOLO727 Charger with mains and car connector
1	Literature pack

Technical specifications**Electrical**

Charging set operating voltage	
• Alternating voltage	110 to 240 V AC 50/60 Hz, 0.6 A
• Direct voltage	13.8 V DC, 2.3 A

Mechanical

Weight	
• Without battery	600 g (21 oz)
• With battery	1.1 kg (38.8 oz)
Dimension (Ø x H)	99.5 mm x 52 mm (3.9 in x 2 in)

Environmental

Operating temperature	5 °C to 45 °C (41 °F to 113 °F)
Storage temperature	-10 °C to 50 °C (14 °F to 120 °F)
Permissible relative humidity	90% (non-condensing)

Trademarks

CAT™ and SOLO™ are trademarks of No Climb Products, Ltd.

Ordering information**SOLO461 Heat detector test kit**

Heat detector tester supplied with one SOLO727 charger and two SOLO 770 battery batons
Order number **SOLO461**

Accessories**SOLO610 Carrying bag**

Robust bag made of sturdy woven polyester for carrying and storing test and service products.
Order number **SOLO610**

SOLO100 Telescopic access pole

Enables the installation and replacement of fire detectors at high ceilings. Expandable with up to three SOLO101 Fixed extension poles. In the Americas, the product is labelled SOLO100. Elsewhere, the product is labelled SOLO106-126.
Order number **SOLO100**

SOLO101 Extension pole

Enables the installation and replacement of fire detectors on ceilings. Expandable with other fixed extension poles. A SOLO101 is supplied in America, while a SOLO107 is supplied elsewhere.
Order number **SOLO101**

SOLO770 Spare battery baton

Rechargeable battery baton for SOLO460 heat detector tester
Order number **SOLO770**

Represented by:

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
emea.securitysystems@bosch.com
emea.boschsecurity.com

Germany:
Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn
Germany
www.boschsecurity.com

North America:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.us

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia